


INTERIOR LED RECESSED DOWN SPOTLIGHT

L03014



- IP54
- CLASS III
- Europe Standard & CE Certificate. 220-240V 50/60Hz
- Aluminium die casting material and powder coating
- Ceiling recessed, Ceiling thickness 3-25mm
- 400-600mm cable with quick connector
- CREE branded COB LED 3SDCM CRI90+
- Ø70mm
- Remote LED Driver
- 0/1-10V I Triac I DALI Tunable white dimming


HIGH LEVEL OF VISUAL COMFORT AND UNIFORM DISTRIBUTION



Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L03014 -7	7W	600lm	Ø 75xH110mm	Ø 70mm	150mA
L03014 -12	12W	1080lm	Ø 75xH110mm	Ø 70mm	300mA

FEATURES

The spotlight comprise a LED light module and a metal mounting frame. The spotlight achieved 25°adjustable. Easy installation. High Definition optical lenses in thermoplastic material. Specialized optics and optical filters can be ordered. Homogeneous and uniform light distribution. Excellent colour rendering ,it's perfect for a wide range of food, flowers, clothes, and in general for other display lighting applications. On the request it can be offered in any RAL colour, matching the specific look and feel of your design. IP54 rating means that they can be used even in bathroom or other damp indoor locations. This enables you to continue the ceiling uniformity throughout bathrooms, wellness areas and other indoor damp locations. Dimmable

Remote LED Driver	Accessoires	Beam Angle	Color Temperature	Finishes
7W 150mA 12W 300mA	 Hex Louver	