


INTERIOR LED RECESSED DOWN SPOTLIGHT

L03033



- IP54
- CLASS III
- Europe Standard & CE Certificate. 220-240V 50/60Hz
- Aluminium die casting and powder coating.
- Ceiling recessed, Plaster -in. Trimless
- 5years Warranty
- COB LED 3SDCM CRI90
- Flicker Free, Remote LED Driver version. PF0.95
- Deeply recessed light source. Visual comfort.
- DALI Dimming from 0~100%, down to 0.01%.

UNIFORM DISTRIBUTION AND SOFT LIGHT



| Code       | System Power<br>W | Output Lumen<br>lm | Dimension<br>mm | Cut Hole<br>mm | Power Supply<br>mA |
|------------|-------------------|--------------------|-----------------|----------------|--------------------|
| L03033 -7  | 7W                | 650lm              | Ø 124xH110mm    | Ø 75mm         | 150mA              |
| L03033 -12 | 12W               | 1100lm             | Ø 124xH110mm    | Ø 75mm         | 300mA              |

FEATURES

Adjustable spotlight, trimless, visual comfort, recessed light source. They comprise a LED light module, a metal baffle and a metal mounting frame. Easy installations. it facilitates the installation by giving the opportunity to the installer to place the mounting frame in advance. No need to worry for the lighting modules in further finishing of the room, as the spotlight modules can be clicked into the frame afterwards, and easy to take it off the mounting frame. The possibility to take the spotlight out from its mounting frame, adjustable and the right angled inclination make this product to be highly flexible and easy to handle. One housing achieved multiple options and different light distributions for a wide variety of applications. The spotlight offer homogeneous and uniform light distribution. Specialized optics and optical filters can be ordered. Flicker-Free. Dimmable. High-quality mixing effect achieved. White and bright to warm and dim, tunable white gives character to its environment. The light spot remain the same while the color change, and there is almost no effect on the light spot. The edge is cut off, the outline of the time spot range is clearly visible when washing the wall, and the interior is uniformly transitioned. Achieve a pleasing and soft effect of the wall washing spot. Dimming from 0~100%, down to 0.01%. 5years warranty. Customized color finishing, power changes are possible depending on the request and the quantity. Moreover, the IP54 rating means that they can be used even in bathroom or other damp indoor locations. This enables you to continue the ceiling uniformity throughout bathrooms, wellness areas and other indoor damp locations. The new creating that meets the needs of your residential and commercial projects.

| Remote LED Driver     | Accessoires | Beam Angle               | Color Temperature                         | Finishes                     |
|-----------------------|-------------|--------------------------|-------------------------------------------|------------------------------|
| 7W 150mA<br>12W 300mA | Hex Louver  | 15°<br>24°<br>36°<br>55° | 2700K<br>3000K<br>4000K<br>5000K<br>6000K | Black<br>White<br>Customized |