


INTERIOR LED RECESSED DOWN SPOTLIGHT

L03091



- IP54
- CLASS III
- Europe Standard & CE Certificate. 220-240V 50/60Hz
- Aluminium die casting material and powder coating
- Ceiling recessed, Ceiling thickness 3-25mm
- 400-600mm cable with quick connector
- Famous brand COB LED 3SDCM CRI90
- Flicker Free, Remote LED Driver version.
- 145x75mm
- 0/1-10V I Triac I DALI Tunable white dimming

VISUAL COMFORT AND UNIFORM DISTRIBUTION



Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L03092 -12	2x12W	2200lm	□ 156x81xH92mm	□ 145x75mm	300mA

FEATURES

Double spotlight, fixed, recessed light source. Luminaires in this line have modular design. They comprise a LED light module and a metal mounting frame. One housing achieved multiple options and different light distributions for a wide variety of applications, the new creating that meets the needs of your residential and commercial projects. The spotlight offer homogeneous and uniform light distribution. deep cut-off angle 45°. easy installations. High Definition optical lenses in thermoplastic material. Specialized optics and optical filters can be ordered. 5years warranty. Flicker-Free. The standard product comes in RAL 9005 Black color finishing I RAL 9016 White color finishing. On the request it can be offered in any RAL colour, matching the specific look and feel of your design. Moreover, the IP54 means that they can be used even in bathroom or other damp indoor locations. This enables you to continue the ceiling uniformity throughout bathrooms, wellness areas and other indoor damp locations. Excellent colour rendering , it's perfect for a wide range of food, flowers, clothes, and in general for other display lighting applications. High-quality mixing effect achieved. White and bright to warm and dim, tunable white gives character to it's environment. The light spot are remain the same while the color change, and there is almost no effect on the light spot. The edge is cut off, the outline of the time spot range is clearly visible when washing the wall, and the interior is uniformly transitioned. Achieve a pleasing and soft effect of the wall washing spot. Dimmable.

Remote LED Driver	Accessoires	Beam Angle	Color Temperature	Finishes
12W 300mA	 Hex Louver	 15°  24°  36°  60°	 2700K  3000K  4000K  5000K  6000K	 Black  White Customized