


INTERIOR LED RECESSED DOWN SPOTLIGHT

L03156



- IP44
- CLASS III
- Europe Standard & CE Certificate. 220-240V 50/60Hz
- Aluminium material and powder coating.
- Ceiling recessed, Trimless
- 24°adjustable lighting fixture
- CITIZEN COB LED 3SDCM CRI90
- Flicker Free, Remote LED Driver version.
- Recessed light source. High level of visual comfort.
- 0/1-10V I Triac I DALI dimming.













UNIFORM DISTRIBUTION AND SOFT LIGHT



Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L03156 -7	7W	350lm	Ø 75xH96mm	Ø 55mm	150mA
L03156 -10	10W	500lm	Ø 75xH96mm	Ø 55mm	250mA

FEATURES

24°adjustable | Trimless spotlight with decorative metal baffle. LED modular design, comprise a LED light module, a metal baffle and a mounting frame. Visual comfort low glare optic with recessed light source. High Definition optical lenses in thermoplastic material. The lock connection design between the installation kit and the spotlight ensures safety and easy installations, easy to take the spot out from its frame. Invisible transition between the fixture and the ceiling. Customized color finishing, power changes are possible depending on the request and the quantity. Dimmable

Remote LED Driver	Accessories	Beam Angle	Color Temperature	Finishes
7W 150mA 10W 250mA	 Hex Louver	 15°  24°  38°  55°	 2700K  3000K  4000K  5000K  6000K	 Black  White Customized