

INTERIOR LED RECESSED DOWNLIGHT

L03165



- IP44
- CLASS III
- Ceiling, wall recessed. Trimless | Plaster-in
- Aluminium lighting fixture, powder coated.
- Flicker Free
- Eyes friendly CE certificate RoHS standard
- CRI97 3SDCM CITIZEN COB LED
- DALI Triac | 0/1-10V | DALI dimmable
- Tunable White dimming
- Warranty 5 Years

HIGH LUMINOUS EFFICIENCY AND UNIFORM DISTRIBUTION.



Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L03165-5	5W	450lm	Ø78xH116mm	Ø55mm	120mA
L03165-9	9W	900lm	Ø78xH136mm	Ø55mm	250mA
L03165-12	12W	1300lm	Ø78xH165mm	Ø55mm	350mA
L03165-20	20W	1700lm	Ø78xH187mm	Ø55mm	500mA

FEATURES

The spotlight achieved 90°adjustable 355°rotation, An ideal accent lighting in residential or commercial. - it provides a high level of visual comfort, the high performances and flexibility for every project metal baffle offered anti-glare, -It is presented to its customers as a clean and non-dazzling product. -Realize superior lighting space with a deep cut-off angle.High Definition optical lenses in thermoplastic material. -Uniform distribution. -Specialised optics and optical filters can be ordered. -Realize superior lighting space with a deep cut-off angle White OR Black color finishing as standard. -Customized power changes are possible depending on the request and the quantity. -On the request it can be offered in any RAL colour, matching the specific look and feel of your design.

Remote LED Driver	Accessoires	Beam Angle	Color Temperature	Finishes
5W 120mA 9W 250mA 12W 350mA 20W 500mA	Softening Lens Hex Louver Prismatic Spread Linear Spread	15° 24° 38° 55°	2700K 3000K 4000K 5000K 6000K	Black White Customized