

INTERIOR LED RECESSED DOWN SPOTLIGHT

L03243



-  IP65
-  CLASS III
-  Europe Standard & CE Certificate. 220-240V 50/60Hz
-  Aluminium die casting material and powder coating
-  Ceiling recessed, Ceiling thickness 3-25mm
-  400-600mm cable with quick connector
-  Famous brand COB LED 3SDCM CRI90
-  Flicker Free, Remote LED Driver version.
-  Recessed light source , eyes friendly
-  0/1-10V | Triac | DALI Tunable white dimming

UNIFORM DISTRIBUTION | IP65



Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L03243 -15	15W	1300lm	Ø92xH78mm	Ø80mm	350mA
L03243 -25	25W	2250lm	Ø123xH93mm	Ø110mm	650mA
L03243 -40	40W	3600lm	Ø145xH106mm	Ø130mm	1000mA

FEATURES

Fixing spotlight , recessed light source. high efficiency of the LED module and reflector, it meets the needs of your residential and commercial projects. protection type IP65. the housing with a separate IP RATED control gear unit. It means that they can be used even in bathroom or other damp indoor locations. This enables you to continue the ceiling uniformity throughout bathrooms, wellness areas and other indoor damp locations. The standard product comes in RAL 9005 Black | RAL 9016 White. Customized color finishing, power changes are possible depending on the request and the quantity.

Remote LED Driver





15W 350mA
25W 650mA
40W 1000mA

Accessoires








Hex Louver

Beam Angle

-  15°
-  24°
-  36°
-  60°

Color Temperature

-  2700K
-  3000K
-  4000K
-  5000K
-  6000K

Finishes

-  Black
-  White
-  Customized