


IN-TRACK DRIVER LED TRACKSPOTLIGHT

L03280



- IP44
- CLASS III
- European standard 3-phase track rails
- ECO Energy Saving. I CE certificate I RoHS standard
- Aluminium cold forging and powder coating housing.
- An ideal solution for accent lighting
- Famous brand COB LED Chips CRI90+ 3SDCM
- Integrated DALI dimm LED Driver I Flicker Free
- Double adjustability 90°adjustable 355°rotation
- Warranty 5Years

EXCELLENT COOLING SYSTEM AND UNIFORM DISTRIBUTION



Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L03280 -19	19W	2500lm	Ø 90x145mm	Ø mm	450mA
L03280 -25	25W	3200lm	Ø 90x145mm	Ø mm	550mA

FEATURES

European standard 3-phase trackspotlight, Aluminium lighting fixture, cold forging process and powder coated, Integrated cooling system to ensure the spotlight long lifetime. Luminaires are powered by a Integrated on/off Driver and adaptor. An ideal solution for accent lighting. the high performances and flexibility for every project. High Definition optical reflector in aluminium material. -Uniform distribution. It allows 360°rotation about the vertical axis and 90° tilting relative to the horizontal plane make the spotlight highly flexible and easy to handle, the light is emitted exactly where you want it. Specialized optical filters can be ordered. The light spots were natural transition, clear and soft. 3SDCM to ensure color temperature consistency for the quality lighting. Excellent colour rendering with CRI90+, it's perfect for a wide range of food, flowers, clothes, and in general for other display lighting applications. The standard product comes in RAL 9005 Black color finishing I RAL 9016 White color finishing. On the request it can be offered in any RAL colour, matching the specific look and feel of your design.

IN-TRACK DRIVER LED TRACKSPOTLIGHT	Accessoires	Beam Angle	Color Temperature	Finishes
19W 450mA 25W 550mA	Hex Louver	15° 24° 36° 60°	2700K 3000K 4000K 5000K 6000K	Black White Customized