

INTERIOR LED RECESSED DOWN SPOTLIGHT

L03344



- IP40
- CLASS III
- Europe Standard & CE Certificate. 220-240V 50/60Hz
- 90° vertical tilting, 360° horizontal rotation and pull-out
- Ceiling Recessed.
- Aluminium die-casting lighting fixture, powder coated.
- CREE branded COB LED CRI90+ 3SDCM
- Flicker Free | Deeply recessed light source.
- Remote LED Driver
- DALI | Triac | 0/1-10V | CASAMBI | DT8

HIGHLY FLEXIBLE AND UNIFORM DISTRIBUTION

Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L03344-5	2x5W	1000lm	□ 43x96xH87mm	□ 35x88mm	125mA
L03344-6	2x6W	1200lm	□ 53x118xH93mm	□ 45x110mm	150mA
L03344-7	2x7W	1260lm	□ 72x131xH110mm	□ 65x121mm	175mA

FEATURES

Double adjustability, 90° vertical tilting and 360° horizontal rotation and pull-out spotlight, Visual comfort low glare optic, recessed light source. available for four different output beams 15/24/36/50°. The basic model comes in white and black colors. Customized color finishing, power changes are possible depending on the request and the quantity. Simple installation with spring, A small downlight characterized by innovative and surprising solutions. The rotation and the right angled inclination make this product to be highly flexible and easy to handle. It is ideal for lighting architectural and artistic details up. High Definition optical lenses in thermoplastic material, uniform distribution. Famous brand LED chips CRI90+ 3steps. Smart lighting, achieved CASAMBI | DALI DT8 dimmable. Easy lighting demand, for a wide scale of projects, from hotels, retail, commercial areas and much more. The spotlight is presented to its customers as a clean and non-dazzling product.

Remote LED Driver	Accessoires	Beam Angle	Color Temperature	Finishes
5W 125mA 6W 150mA 7W 175mA	Hex Louver	15° 24° 36° 50°	2700K 3000K 4000K 5000K 6000K	Black White Customized