


INTERIOR LED RECESSED DOWN SPOTLIGHT

L03350



- IP40
- CLASS III
- Europe Standard & CE Certificate. 220-240V 50/60Hz
- 90° vertical tilting, 360° horizontal rotation and pull-out
- Ceiling Recessed.
- Aluminium lighting fixture, powder coated.
- COB LED CRI90+ 3SDCM
- Flicker Free I Deeply recessed light source.
- Remote LED Driver
- DALI I Triac I 0/1-10V I CASAMBI I DT8

HIGHLY FLEXIBLE AND UNIFORM DISTRIBUTION



Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L03350 -9	9W	900lm	Ø 38xH80mm	Ø 55mm	225mA

FEATURES

Double adjustability, 90°adjustable 355°rotation spotlight , Visual comfort low glare optic , recessed light source. available for four different output beams 15/24/36/50°. The basic model comes in white and black colors. Customized color finishing, power changes are possible depending on the request and the quantity. Simple installation with spring. A small downlight characterized by innovative and surprising solutions.The rotation and the right angled inclination make this product to be highly flexible and easy to handle.It is ideal for lighting architectural and artistic details up. High Definition optical lenses in thermoplastic material,uniform distribution. Famous brand LED chips CRI90+ 3steps. Smart lighting, achieved CASAMBI I DALI DT8 dimmable. Easy lighting demand, for a wide scala of projects, from hotels, retail , commercial areas and much more. The spotlight is presented to its customers as a clean and non-dazzling product.

Remote LED Driver	Accessoires	Beam Angle	Color Temperature	Finishes
9W 225mA	 Hex Louver	 15°  24°  36°  50°	 2700K  3000K  4000K  5000K  6000K	 Black  White Customized