

INTERIOR LED RECESSED DOWN SPOTLIGHT

L03376



- IP20
- CLASS III
- Europe Standard & CE Certificate. 220-240V 50/60Hz
- Aluminium die casting material and powder coating
- Ceiling recessed, Ceiling thickness 3-25mm
- 400-600mm cable with quick connector
- COB LED 3SDCM CRI90+
- Flicker Free, Remote LED Driver version.
- 30°adjustable
- 0/1-10V I Triac I DALI dimmable

UNIFORM DISTRIBUTION

Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L03376-7	7W	700lm	□ 84x84xH35mm	□ 75x75mm	130mA
L03376-15	15W	1500lm	□ 105x105xH35mm	□ 95x95mm	350mA

FEATURES

30° adjustable spotlight remote LED Driver version. Slim trim, height reduced. High Definition optical lenses in thermoplastic material. The spotlight offer homogeneous and uniform light distribution. Excellent colour rendering , it's perfect for a wide range of food, flowers, clothes, and in general for other display lighting applications. High-quality mixing effect achieved. White and bright to warm and dim, tunable white gives character to its environment. The light spot are remain the same while the color change, and there is almost no effect on the light spot. The edge is cut off, the outline of the time spot range is clearly visible when washing the wall, and the interior is uniformly transitioned. Achieve a pleasing and soft effect of the wall washing spot. Dimming from 0~100%, down to 0.01%. On the request it can be offered in any RAL colour, matching the specific look and feel of your design.

Remote LED Driver	Accessoires	Beam Angle	Color Temperature	Finishes
7W 130mA 15W 350mA		15° 24° 36° 60°	2700K 3000K 4000K 5000K 6000K	Black White Customized