


INTERIOR LED RECESSED DOWN SPOTLIGHT

L03379



- IP40
- CLASS III
- Europe Standard & CE Certificate. 220-240V 50/60Hz
- 45° vertical tilting, 360° horizontal rotation
- Ceiling Recessed.
- Aluminium die-casting lighting fixture, powder coated.
- Philips branded COB LED CRI90+ 3SDCM
- Flicker Free | Deeply recessed light source.
- Remote LED Driver
- DALI | Triac | 0/1-10V | CASAMBI | DT8

HIGHLY FLEXIBLE AND UNIFORM DISTRIBUTION



Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L03379-30	30W	2700lm	∅ 140xH120mm	∅ 120mm	750mA
L03379-35	35W	3200lm	∅ 165xH120mm	∅ 145mm	900mA
L03379-40	40W	3600lm	∅ 165xH120mm	∅ 145mm	1000mA

FEATURES

Aluminium die casting material and powder coating. Remote LED driver version. Metal baffle, double adjustability, 45° vertical tilting and 355° horizontal rotation spotlight, Visual comfort low glare optic with recessed light source. available for three different output beams 15/24/36°. The basic model comes in white and black colors. Customized color finishing, power changes are possible depending on the request and the quantity. Simple installation ceiling recessed with spring, A small downlight characterized by innovative and surprising solutions. The rotation and the right angled inclination make this product to be flexible and easy to handle. It is ideal for lighting architectural and artistic details up. High Definition optical lenses in thermoplastic material, uniform distribution. Famous brand LED chips CRI90+ 3steps. Smart lighting, achieved CASAMBI | DALI DT8 dimmable. Easy lighting demand, for a wide scala of projects, from hotels, retail, commercial areas and much more. The spotlight is presented to its customers as a clean and non-dazzling product.

Remote LED Driver

30W 750mA
35W 900mA
40W 1000mA

Accessoires



Beam Angle

- 15°
- 24°
- 36°

Color Temperature

- 2700K
- 3000K
- 4000K
- 5000K
- 6000K

Finishes

- Black
- White
- Customized