


## INTERIOR LED RECESSED DOWN SPOTLIGHT

L03388



- IP20
- CLASS III
- CEILING RECESSED
- 400-600mm cable with quick connector.
- 136x43 mm
- Eyes friendly CE certificate RoHS standard
- CRI90+ Bridgelux branded SMD
- DALI Triac I 0/1-10V I DALI dimmable
- Tunable White dimming
- Warranty 5 Years

### UNIFORM DISTRIBUTION



136x43mm

Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L03388-10	6x2W	800lm	□ 141x49xH44mm	□ 136x43mm	600mA

### FEATURES

Adjustable slim trim spotlight, an ideal accent lighting in residential or commercial areas. Aluminium die casting lighting fixture, powder coated. Remote LED driver version. Flicker-Free. This innovative optic combines aesthetic and performance functions by embellishing ceilings and spaces along side visual comfort and very high lighting efficiency. Design the essential, linear form combines with an impressive aesthetic finish where light creates a magical play of reflections. Opti Diamond revolutionizes the visual perception of space and enhances well-being and efficiency. One housing, multiple options, with different light distributions for a wide variety of applications. Version Wall Washer or Version for general lighting. Uniform distribution. Optic in PC. Visual comfort low glare optic with deeply recessed light source. UGR<19. Steel wire springs for easy installation. 6LEDs, 18V, CRI90 10W White | Black color finishing as standard. Customized color finishing, power changes are possible depending on the request and the quantity.

Remote LED Driver	Accessoires	Beam Angle	Color Temperature	Finishes
2W 600mA		24° 36°	2700K 3000K 4000K 5000K 6000K	Black White Customized