

## INTERIOR LED RECESSED DOWN SPOTLIGHT

L03652



- IP20
- CLASS III
- Europe Standard & CE Certificate. 220-240V 50/60Hz
- Aluminium die casting material and powder coating
- Ceiling recessed, Ceiling thickness 3-25mm
- 400-600mm cable with quick connector
- Famous brand COB LED 2SDCM
- Flicker Free, Remote LED Driver version.
- Deeply recessed light source. High level of visual comfort
- 0/1-10V I Triac I DALI Tunable white dimming

### HIGH LEVEL OF VISUAL COMFORT AND UNIFORM DISTRIBUTION

Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L03652-10	2x10W	1600lm	□ 65x122xH80mm	□ 55x112mm	250mA
L03652-15	2x15W	2400lm	□ 85x162xH90mm	□ 75x152mm	300mA
L03652-30	2x30W	4800lm	□ 105x202xH100mm	□ 95x192mm	750mA
L03652-40	2x40W	6400lm	□ 130x250xH115mm	□ 115x240mm	1000mA

### FEATURES

Die casting aluminum material and powder coating. Double adjustability, 45°adjustable 360°rotation spotlight, Luminaires in this line have modular design. They comprise a LED light module, a metal baffle and a metal mounting frame. One housing achieved multiple options and different light distributions for a wide variety of applications, the new creating that meets the needs of your residential and commercial projects. The spotlight offer homogeneous and uniform light distribution. deep cut-off angle 68°. High level of visual comfort low glare optic with recessed light source. Achieved visible lighting effect, invisible lighting fixtures. High Definition optical lenses in thermoplastic material. cross lighting. Specialized optics and optical filters can be ordered. Available for four different output beams 15/24/36/55°. The decorative secondary optic available in multiple color finishing, Black I White I Chromed Silver. The basic model comes in white color. Customized color finishing, power changes are possible depending on the request and the quantity. Simple installation with spring. The rotation and the right angled inclination make this product to be highly flexible and easy to handle. It is presented to its customers as a clean and non-dazzling product. Famous brand LED chips CRI90+ 2steps. Smart lighting, achieved CASAMBI I DALI DT8 dimmable.

Remote LED Driver	Accessoires	Beam Angle	Color Temperature	Finishes
10W 250mA 15W 300mA 30W 750mA 40W 1000mA	Hex Louver	<input type="checkbox"/> 15° <input type="checkbox"/> 24° <input type="checkbox"/> 36° <input type="checkbox"/> 55°	<input type="checkbox"/> 2700K <input type="checkbox"/> 3000K <input type="checkbox"/> 4000K <input type="checkbox"/> 5000K <input type="checkbox"/> 6000K	<input checked="" type="checkbox"/> Black <input type="checkbox"/> White Customized