


INTERIOR LED OFFICE LIGHTING

L05089



- IP40
- CLASS III
- Surface Mounted | Ceiling Suspended (cable L1500mm)
- 220-240V 50/60Hz 20V-54V DC
- Aluminium extrusion material and powder coating
- Eyes friendly CE certificate RoHS standard
- Famous brand LED CRI90+
- DALI Triac | 0/1-10V | DALI | CASAMBI
- Customized color finishing and power are acceptable
- Warranty 5 Years

HIGH EFFICIENCY | UNIFORM DISTRIBUTION | LOW GLARE



Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L05089-33	33W	3960lm	□ W35xH28xL1170mm	□ mm	850mA
L05089-28	28W	3360lm	□ W35xH28xL1170mm	□ mm	750mA

FEATURES

Uniformity and contrast are key aspects of the office lighting to ensure safe environment. The correct lighting creates an atmosphere that provides employee with positive work environment and increase employee satisfaction and productivity. Downlight | UGR<19 | CRI90 | 120lm/W L05089 is a single lighting solution with linear down option. Design the essential, linear form combines with an impressive aesthetic finish where light creates a magical play of reflections. Strict glare control UGR<19, Antiglare lens, made by contrasted materials. Come together in a single miniaturized transparent component. High efficiency Up to 91%, High efficacy Up to 120lm/W, CRI90. Excellent cooling system. Aluminium extrusion material and powder coating. Die-cast aluminium sealing caps. with no visible screw design. Remote LED Driver version. Reduced materials diversity Reduced dimensions and reduced weight. The standard length of lighting fixture is L1170mm. W35xH28mm. The basic model comes in matt white or matt black color finishing. Customized color finishing | power | length of lighting fixture are possible depending on the request and the quantity to match the specific look and feel of your design. Light management via wireless systems allows technology to be integrated easily and flexibly, without the constraints of wiring. Thanks to the user-friendly, optionally available control systems, CASAMBI which can be switch on and off using dimming panel or Casambi APP. Ceiling Suspended | Ceiling Mounted installation. Standard length of cable L1200mm for ceiling suspended installation. Warranty 5years | Leadtimes 7-10 business days.

Remote LED Driver	Accessoires	Beam Angle	Color Temperature	Finishes
33W 850mA 28W 750mA	Hanging wire 5-piece set (Steel wire suspension wire 1.5mm by default)	<input type="checkbox"/> 15° <input checked="" type="checkbox"/> 24° <input checked="" type="checkbox"/> 36°	<input checked="" type="checkbox"/> 2700K <input type="checkbox"/> 3000K <input type="checkbox"/> 4000K <input type="checkbox"/> 5000K <input type="checkbox"/> 6000K	<input checked="" type="checkbox"/> Black <input type="checkbox"/> White Customized