


SURFACE MOUNTED LED DOWN SPOTLIGHT - IP54

L08053



- IP54
- CLASS III
- Europe Standard & CE Certificate. 220-240V 50/60Hz
- IP54 | 25° adjustable and 360° rotation
- Surface Mounted
- Aluminium die-casting lighting fixture, powder coated.
- Famous brand LED CRI90+ 2SDCM UGR<16
- Flicker Free | Deeply recessed light source.
- Built-in LED Driver
- DALI | Triac | 0/1-10V | CASAMBI

IP54 AND UNIFORM DISTRIBUTION



Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L08053 -7	3x7W	2100lm	□ W100xH100xL290mm	□ mm	150mA
L08053 -12	3x12W	3600lm	□ W100xH100xL290mm	□ mm	300mA

FEATURES

Surface mounted adjustable spotlight with recessed light source UGR<16. 25° adjustable and 360° rotation. IP54 rated, It offers more than four beam angles: 15° 24° 36° and 55°, delivering highly uniform light distribution. This high-efficiency spotlight achieves up to 100lm/W. Constructed with die-cast aluminum and powder coating, metal baffle available in multiple colors. The LED driver is built-in. The standard version comes in white and black, while customized colors and adjustable power are supported based on customer requirements and order quantity. It adopts high-brand LED chips with CRI90+ and 2step binning. Supports smart lighting systems, compatible with CASAMBI and DALI dimming, the IP54 rating means that they can be used even in bathroom or other damp indoor locations. This enables you to continue the ceiling uniformity throughout bathrooms, wellness areas and other indoor damp locations. The new creating that meets the needs of your residential and commercial projects. The spotlight features a clean design and excellent anti-glare performance, providing comfortable, non-dazzling lighting. An ideal engineering lighting solution for the mid-to-high-end market. 5-year warranty provided.

Built-in LED Driver	Accessoires	Beam Angle	Color Temperature	Finishes
7W 150mA 12W 300mA	Hex Louver	15° 24° 36° 55°	2700K 3000K 4000K 5000K 6000K	Black White Customized

