


## INTERIOR LED SPOTLIGHT

L70103



- IP54
- CLASS III
- Surface Mounted Installation
- ECO Energy Saving
- Flicker Free
- Eyes friendly CE certificate RoHS standard
- CRI90+ OSRAM SMD LED
- Europe Standard & CE Certificate. DC12-24V.
- 400-600mm cable with quick connector
- DALI I Triac I 0/1-10V dimmable

An ideal accent lighting in residential or commercial places



Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L70103 -3	3W	190lm	∅ 25xH60mm	∅ mm	500mA
L70103 -5	5W	400lm	∅ 25xH60mm	∅ mm	600mA

### FEATURES

Adjustable LED spot lighting, Aluminium materials -black color finishing as standard. Customized color finishing, is possible depending on the request and the quantity. - Matched main dimming and Dali dimming, surface mounted installation as standard. Insert into the ground or recessed can be customized. Lens version,30° output for a better visual comfort. lighting fixture is 80° adjustable and 355°rotatable, suitable for light up anyway where. 50000hours life time.

#### Remote LED Driver

3W 500mA  
5W 600mA

#### Accessoires

#### Beam Angle



#### Color Temperature

- 2700K
- 3000K
- 4000K
- 5000K
- 6000K

#### Finishes

- Black
- White
- Customized