



W100xL100xH100
L08051 9W 024



W100xL196xH100
L08052 18W 024



W100xL290xH100
L08053 27W 024



W195xL195xH120
L08054 36W 024



55xH90
L08106 10W 025



190x62xH115
L08107 20W 025



251x62xH115
L08108 30W 025



208x62xH115
L08109 40W 025



56x250xH30
L08101 36W 026



56x380xH26
L08102 24W 026



56x580xH26
L08103 36W 026



100xH100
L08027 9W 026



100x210xH96
L08028 18W 027



100x320xH96
L08152 27W 027




100x180xH96
L08153 27W 027



100x180xH96
L08154 36W 027



170x85xH88
L08411 12W 028



220x85xH88
L08412 24W 028



220x220xH88
L08413 36W 028



355x85xH88
L08414 36W 028



220x220xH88
L08415 48W 029



62xH150
L08203 15W 029



42xH883
L08203 7W 029



50*H1500
L08155 10W 029



40xH100
L08163 12W 030



62x100
L08062 12W 030



60xH185
L08118 12W 030



60xH185
L08047 12W 030



79xH110
L08505 12W 031



80xH110
L08054 12W 031



62x171
L08620 12W 031



72xH167
L08621 12W 031



85xH135
L08501 12W 032



65xH120
L08502 10W 032



95xH120
L08058 15W 032



130xH145
L08058 25W 032



160xH180
L08058 30W 033



60xH150
L08059 9W 033



85xH135
L08060 12W 033



95xH120
L08058 18W 033



55xH90
L08180 12W 034



75xH115
L08180 15W 034



95xH150
L08180 24W 034



115xH150
L08180 30W 034



75xH152
L08070 15W 035



95xH152
L08070 20W 035



115xH152
L08070 30W 035



140xH162
L08070 40W 035



130xH100
L08133 10W 036



165xH115
L08133 20W 036



200xH130
L08133 30W 036



90xH90
L08057 9W 036



110xH120
L08057 15W 037



130xH152
L08057 25W 037



170xH185
L08057 35W 037



193xH193
L08057 45W 037



70xH140
L08143 9W 038



100xH140
L08143 15W 038



70xH140
L08004 9W 038



100xH170
L08004 20W 038



98xH90
L08006 15W 039



120xH110
L08006 20W 039



98xH125
L08009 15W 039



147x76xH96
L08221 24W 039



100xH112
L08002 15W 040



120xH133
L08002 20W 040



150xH142
L08002 25W 040



76x76xH150
L08012 12W 041



96x96xH150
L08012 20W 041



116x116xH150
L08012 30W 041



90xH90
L08056 9W 041



110xH120
L08056 20W 042



130xH135
L08056 30W 042



160xH165
L08056 40W 042



273*78*H56
L07134 20W 042



381*78*H56
L07135 30W 043



548*78*H56
L07136 50W 043



85xH88
L08417 12W 043



170x85xH88
L08418 12W 043



210x85xH88
L08419 24W 044



355x85xH88
L08420 36W 044



220x220xH88
L08421 48W 044



140*37*H86
L07146 10W 044



272*37*H86
L07147 20W 045



405*37*H86
L07148 30W 045



120xW42xH66
L07150 9W 045



195xW42xH66
L07151 15W 045



385xW42xH66
L07152 30W 046



120*120*H90
L07170 36W 046



82*82*H80
L07169 16W 046



51x51xH85
L07167 8W 046



70 x70xH85
L07168 14W 047



96*96*H83
L07142 18W 047



66*66*H83
L07140 8W 047



70*H83
L07141 8W 047



 78xH58
L07153 7W 048



 100xH58
L07154 12W 048



 115xH58
L07155 18W 048



 160xH58
L07156 24W 048



 95xH59
L07159 18W 049



 112xH60
L07160 20W 049



 157xH69
L07161 30W 049




 202xH70
L07162 40W 049



INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT



L08051 - 9



W100xL100xH100

power	driver	lumen	size(mm)	LEDs	beam angle
9W	250mA	765lm 4000K	W100xL100xH100	1	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.73kgs					


L08052 - 18



W100xL196xH100

power	driver	lumen	size(mm)	LEDs	beam angle
18W	500mA	1530lm 4000K	W100xL196xH100	2	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
1.32kgs					


L08053 - 27



W100xL290xH100

power	driver	lumen	size(mm)	LEDs	beam angle
27W	750mA	2295lm 4000K	W100xL290xH100	3	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
1.95kgs					

L08054 - 36



W195xL195xH120


power	driver	lumen	size(mm)	LEDs	beam angle
36W	1050mA	3060lm 4000K	W195xL195xH120	4	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
2.54kgs					

Built-in Driver	LED	Accessories	Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 	 Linear Spread Hex Louver Prismatic Spread Softening Lens	 Matt white Matt black Customized	 2700K 3000K 4000K 5000K	CRI90+
024		 WH/BK WH BK	*It allows you to match the fixture with its surroundings.		



INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT

L08106 -10



55xH90

power	driver	lumen	size(mm)	LEDs	beam angle
10W	250mA	850lm 4000K	55xH90	1	
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					

L08107 -20



190x62xH115

power	driver	lumen	size(mm)	LEDs	beam angle
20W	500mA	1700lm 4000K	190x62xH115	2	
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					

L08108 -30



251x62xH115

power	driver	lumen	size(mm)	LEDs	beam angle
30W	750mA	2550lm 4000K	251x62xH115	3	
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					

L08109 -40



208x62xH115

power	driver	lumen	size(mm)	LEDs	beam angle
40W	750mA	3400lm 4000K	208x62xH115	4	
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					


Built-in Driver	LED	Accessories				Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 					Matt white Matt black Customized	2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.



INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT


L08101 - 36



56x250xH30

power	driver	lumen	size(mm)	LEDs	beam angle
36W	900mA	3060lm 4000K	56x250xH30	3	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					


L08102 - 24



56xW380xH26

power	driver	lumen	size(mm)	LEDs	beam angle
24W	600mA	2040lm 4000K	56xW380xH26	2	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					


L08103 - 36



56xW580xH26

power	driver	lumen	size(mm)	LEDs	beam angle
36W	900mA	3060lm 4000K	56xW580xH26	3	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					

L08027 - 9



100xH100

power	driver	lumen	size(mm)	LEDs	beam angle
9W	225mA	765lm 4000K	100xH100	1	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					


Built-in Driver	LED	Accessories				Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 					 Customized	 	CRI90+

*It allows you to match the fixture with its surroundings.




INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT

L08028 -18




power	driver	lumen	size(mm)	LEDs	beam angle
18W	450mA	1530lm 4000K	100x210xH96	2	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					

L08152 -27



power	driver	lumen	size(mm)	LEDs	beam angle
27W	675mA	2295lm 4000K	100x320xH96	3	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					

L08153 -27



power	driver	lumen	size(mm)	LEDs	beam angle
27W	675mA	2295lm 4000K	100x180xH96	3	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					

L08154 -36



power	driver	lumen	size(mm)	LEDs	beam angle
36W	900mA	3060lm 4000K	100x180xH96	3	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					

Built-in Driver	LED	Accessories				Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 					Matt white Matt black Customized	2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.



INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT

L08411 - 12



170x85xH88

power	driver	lumen	size(mm)	LEDs	beam angle
12W	300mA	1020lm 4000K	170x85xH88	1	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CE CRI >97					
0.00kgs					

L08412 - 24



220x85xH88

power	driver	lumen	size(mm)	LEDs	beam angle
24W	600mA	2040lm 4000K	220x85xH88	2	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CE CRI >97					
0.00kgs					

L08413 - 36



220x220xH88

power	driver	lumen	size(mm)	LEDs	beam angle
36W	900mA	3060lm 4000K	220x220xH88	3	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CE CRI >97					
0.00kgs					

L08414 - 36



355x85xH88

power	driver	lumen	size(mm)	LEDs	beam angle
36W	900mA	3060lm 4000K	355x85xH88	3	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CE CRI >97					
0.00kgs					

Built-in Driver	LED	Accessories				Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 					Matt white Matt black Customized	2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.



INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT


L08415 -48



220x220xH88

power	driver	lumen	size(mm)	LEDs	beam angle
48W	1200mA	4080lm 4000K	220x220xH88	4	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CE CRI >97					


L08203 -15



62xH150

power	driver	lumen	size(mm)	LEDs	beam angle
15W	375mA	1275lm 4000K	62xH150	1	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CE CRI >97					
0.00kgs					


L08203 -7



42xH883

power	driver	lumen	size(mm)	LEDs	beam angle
7W	175mA	595lm 4000K	42xH883	1	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CE CRI >97					
0.00kgs					

L08155 -10



50*H1500

power	driver	lumen	size(mm)	LEDs	beam angle
10W	250mA	850lm 4000K	50*H1500	1	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CE CRI >97					


Built-in Driver	LED	Accessories				Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 					 Customized	 	CRI90+

*It allows you to match the fixture with its surroundings.




INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT

L08163 - 12




power	driver	lumen	size(mm)	LEDs	beam angle
12W	300mA	1020lm 4000K	40xH100	1	 26°
IP44 DALI  FLICKER FREE					
220-240V 50/60Hz  CRI >97					
0.00kgs					

L08062 - 12




power	driver	lumen	size(mm)	LEDs	beam angle
12W	300mA	1020lm 4000K	62x62x100	4	 26°
IP44 DALI  FLICKER FREE					
220-240V 50/60Hz  CRI >97					
0.00kgs					

L08118 - 12



power	driver	lumen	size(mm)	LEDs	beam angle
12W	300mA	1020lm 4000K	60xH185	1	 26°
IP44 DALI  FLICKER FREE					
220-240V 50/60Hz  CRI >97					
0.00kgs					

L08047 - 12



power	driver	lumen	size(mm)	LEDs	beam angle
12W	300mA	1020lm 4000K	60x60xH185	1	 26°
IP44 DALI  FLICKER FREE					
220-240V 50/60Hz  CRI >97					
0.00kgs					


Remote LED Driver	LED	Accessories				Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	  					 Matt white  Matt black Customized	 2700K  3000K  4000K  5000K	CRI90+

*It allows you to match the fixture with its surroundings.




INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT

L08505 -12




power	driver	lumen	size(mm)	LEDs	beam angle
12W	300mA	1020lm 4000K	79xH110	1	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					

L08054 -12




power	driver	lumen	size(mm)	LEDs	beam angle
12W	300mA	1020lm 4000K	80x80xH110	1	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					

L08620 -12



power	driver	lumen	size(mm)	LEDs	beam angle
12W	300mA	1020lm 4000K	62xH171	1	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					

L08621 -12



power	driver	lumen	size(mm)	LEDs	beam angle
12W	300mA	1020lm 4000K	72xH167	1	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					


Built-in Driver	LED	Accessories				Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 					 Customized	 	CRI90+

*It allows you to match the fixture with its surroundings.




INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT

L08501 - 12




power	driver	lumen	size(mm)	LEDs	beam angle
12W	300mA	1020lm 4000K	85xH135	1	26°
IP44 DALI FLICKER FREE 220-240V 50/60Hz CE CRI >97					

L08502 - 10




power	driver	lumen	size(mm)	LEDs	beam angle
10W	250mA	850lm 4000K	65xH120	1	15° 26° 36°
IP44 DALI FLICKER FREE 220-240V 50/60Hz CE CRI >97					

L08058 - 15



power	driver	lumen	size(mm)	LEDs	beam angle
15W	375mA	1275lm 4000K	95xH120	1	15° 26° 36°
IP44 DALI FLICKER FREE 220-240V 50/60Hz CE CRI >97					

L08058 - 25



power	driver	lumen	size(mm)	LEDs	beam angle
25W	625mA	2125lm 4000K	130xH145	1	15° 26° 36°
IP44 DALI FLICKER FREE 220-240V 50/60Hz CE CRI >97					


Built-in Driver	LED	Accessories	Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 	 Linear Spread Hex Louver Prismatic Spread Softening Lens	 Matt white Matt black Customized	 2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.




INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT

L08058 -30




power	driver	lumen	size(mm)	LEDs	beam angle
30W	750mA	2550lm 4000K	160xH180	1	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					

L08059 -9



power	driver	lumen	size(mm)	LEDs	beam angle
9W	225mA	765lm 4000K	60xH150	1	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					

L08060 -12



power	driver	lumen	size(mm)	LEDs	beam angle
12W	300mA	1020lm 4000K	85xH135	1	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					



L08058 -18



power	driver	lumen	size(mm)	LEDs	beam angle
18W	450mA	1530lm 4000K	95xH120	1	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					

Built-in Driver	LED	Accessories	Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 	 Linear Spread Hex Louver Prismatic Spread Softening Lens	 Matt white Matt black Customized	 2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.



INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT

L08180 - 12



55xH90

power	driver	lumen	size(mm)	LEDs	beam angle
12W	300mA	1020lm 4000K	55xH90	1	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CE CRI >97					
0.00kgs					

L08180 - 15



75xH115

power	driver	lumen	size(mm)	LEDs	beam angle
15W	375mA	1275lm 4000K	75xH115	1	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CE CRI >97					
0.00kgs					

L08180 - 24



95xH150

power	driver	lumen	size(mm)	LEDs	beam angle
24W	600mA	2040lm 4000K	95xH150	1	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CE CRI >97					
0.00kgs					

L08180 - 30



115xH150

power	driver	lumen	size(mm)	LEDs	beam angle
30W	750mA	2550lm 4000K	115xH150	1	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CE CRI >97					
0.00kgs					


Built-in Driver	LED	Accessories				Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming						Matt white Matt black Customized	2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.



INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT


L08070 -15



75xH152

power	driver	lumen	size(mm)	LEDs	beam angle
15W	375mA	1275lm 4000K	75xH152	1	
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					


L08070 -20



95xH152

power	driver	lumen	size(mm)	LEDs	beam angle
20W	500mA	1700lm 4000K	95xH152	1	
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					


L08070 -30



115xH152

power	driver	lumen	size(mm)	LEDs	beam angle
30W	750mA	2550lm 4000K	115xH152	1	
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					

L08070 -40



140xH162

power	driver	lumen	size(mm)	LEDs	beam angle
40W	1000mA	3400lm 4000K	140xH162	1	
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					


Built-in Driver	LED	Accessories	Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 	 Linear Spread Hex Louver Prismatic Spread Softening Lens	 Matt white Matt black Customized	 2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.




INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT

L08133 - 10




power	driver	lumen	size(mm)	LEDs	beam angle
10W	250mA	850lm 4000K	130xH100	1	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CE CRI >97					
0.00kgs					

L08133 - 20




power	driver	lumen	size(mm)	LEDs	beam angle
20W	500mA	1700lm 4000K	165xH115	1	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CE CRI >97					
0.00kgs					

L08133 - 30



power	driver	lumen	size(mm)	LEDs	beam angle
30W	750mA	2550lm 4000K	200xH130	1	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CE CRI >97					
0.00kgs					

L08057 - 9



power	driver	lumen	size(mm)	LEDs	beam angle
9W	225mA	765lm 4000K	90xH90	1	26°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CE CRI >97					
0.00kgs					


Built-in Driver	LED	Accessories				Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 					Matt white Matt black Customized	2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.




INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT

L08057 -15




power	driver	lumen	size(mm)	LEDs	beam angle
15W	375mA	1275lm 4000K	110xH120	1	
IP44 DALI FLICKER FREE					
CRI >97					

L08057 -25




power	driver	lumen	size(mm)	LEDs	beam angle
25W	625mA	2125lm 4000K	130xH152	1	
IP44 DALI FLICKER FREE					
CRI >97					
0.00kgs					

L08057 -35



power	driver	lumen	size(mm)	LEDs	beam angle
35W	875mA	2975lm 4000K	170xH185	1	
IP44 DALI FLICKER FREE					
CRI >97					
0.00kgs					

L08057 -45



power	driver	lumen	size(mm)	LEDs	beam angle
45W	1125mA	3825lm 4000K	193xH193	1	
IP44 DALI FLICKER FREE					
CRI >97					


Built-in Driver	LED	Accessories				Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 					Customized		CRI90+

*It allows you to match the fixture with its surroundings.




INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT

L08143 - 9




power	driver	lumen	size(mm)	LEDs	beam angle
9W	225mA	765lm 4000K	70x70xH140	1	26°
IP44 DALI FLICKER FREE 220-240V 50/60Hz CE CRI >97					
0.00kgs					

L08143 - 15




power	driver	lumen	size(mm)	LEDs	beam angle
15W	375mA	1275lm 4000K	100x100xH140	1	26°
IP44 DALI FLICKER FREE 220-240V 50/60Hz CE CRI >97					
0.00kgs					

L08004 - 9



power	driver	lumen	size(mm)	LEDs	beam angle
9W	225mA	765lm 4000K	70x70xH140	1	26°
IP44 DALI FLICKER FREE 220-240V 50/60Hz CE CRI >97					
0.00kgs					

L08004 - 20



power	driver	lumen	size(mm)	LEDs	beam angle
20W	500mA	1700lm 4000K	100x100xH170	1	26°
IP44 DALI FLICKER FREE 220-240V 50/60Hz CE CRI >97					
0.00kgs					


Built-in Driver	LED	Accessories				Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 					Matt white Matt black Customized	2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.




INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT

L08006 -15




power	driver	lumen	size(mm)	LEDs	beam angle
15W	375mA	1275lm 4000K	98x98xH90	1	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					

L08006 -20




power	driver	lumen	size(mm)	LEDs	beam angle
20W	500mA	1700lm 4000K	120x120xH110	1	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					

L08009 -15



power	driver	lumen	size(mm)	LEDs	beam angle
15W	375mA	1275lm 4000K	98x98xH125	1	15° 26° 36° 55°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					

L08221 -24



power	driver	lumen	size(mm)	LEDs	beam angle
24W	600mA	2040lm 4000K	147x76xH96	2	15° 26° 36° 55°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					


Built-in Driver	LED	Accessories	Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 	 Linear Spread Hex Louver Prismatic Spread Softening Lens	 Matt white Matt black Customized	 2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.



INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT


L08002 - 15



100xH112

power	driver	lumen	size(mm)	LEDs	beam angle
15W	375mA	1275lm 4000K	100x100xH112	1	26°
IP44 DALI 220-240V 50/60Hz CE FLICKER FREE CRI >97					


L08002 - 20



120xH133

power	driver	lumen	size(mm)	LEDs	beam angle
20W	500mA	1700lm 4000K	120x120xH133	1	26°
IP44 DALI 220-240V 50/60Hz CE FLICKER FREE CRI >97					

L08002 - 25



150xH142

power	driver	lumen	size(mm)	LEDs	beam angle
25W	625mA	2125lm 4000K	150x150xH142	1	26°
IP44 DALI 220-240V 50/60Hz CE FLICKER FREE CRI >97					


Built-in Driver	LED	Accessories				Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 					Matt white Matt black Customized	2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.




INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT

L08012 -12




power	driver	lumen	size(mm)	LEDs	beam angle
12W	300mA	1020lm 4000K	76x76xH150	1	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					

L08012 -20




power	driver	lumen	size(mm)	LEDs	beam angle
20W	500mA	1700lm 4000K	96x96xH150	1	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					

L08012 -30



power	driver	lumen	size(mm)	LEDs	beam angle
30W	750mA	2550lm 4000K	116x116xH150	1	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					

L08056 -9



power	driver	lumen	size(mm)	LEDs	beam angle
9W	225mA	765lm 4000K	90x90xH90	1	15° 26° 36°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					


Built-in Driver	LED	Accessories				Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 					 Customized	 	CRI90+

*It allows you to match the fixture with its surroundings.



INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT


L08056 - 20



110xH120

power	driver	lumen	size(mm)	LEDs	beam angle
20W	500mA	1700lm 4000K	110x110xH120	1	26° 45°
IP44 DALI FLICKER FREE 220-240V 50/60Hz CRI >97					
0.00kgs					


L08056 - 30



130xH135

power	driver	lumen	size(mm)	LEDs	beam angle
30W	750mA	2550lm 4000K	130x130xH135	1	26° 45°
IP44 DALI FLICKER FREE 220-240V 50/60Hz CRI >97					
0.00kgs					


L08056 - 40



160xH165

power	driver	lumen	size(mm)	LEDs	beam angle
40W	1000mA	3400lm 4000K	160x160xH165	1	26° 45°
IP44 DALI FLICKER FREE 220-240V 50/60Hz CRI >97					
0.00kgs					

L07134 - 20



273*78*H56

power	driver	lumen	size(mm)	LEDs	beam angle
20W	500mA	1700lm 4000K	273*78*H56	4	26° 45°
IP44 DALI FLICKER FREE 220-240V 50/60Hz CRI >97					
0.00kgs					


Built-in Driver	LED	Accessories				Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 					Matt white Matt black Customized	2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.



INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT


L07135 -30



381*78*H56

power	driver	lumen	size(mm)	LEDs	beam angle
30W	750mA	2550lm 4000K	381*78*H56	6	
IP44 DALI FLICKER FREE 220-240V 50/60Hz CRI >97					


L07136 -50



548*78*H56

power	driver	lumen	size(mm)	LEDs	beam angle
50W	1250mA	4250lm 4000K	548*78*H56	10	
IP44 DALI FLICKER FREE 220-240V 50/60Hz CRI >97 0.00kgs					


L08417 -12



85xH88

power	driver	lumen	size(mm)	LEDs	beam angle
12W	300mA	1020lm 4000K	85x85xH88	1	
IP44 DALI FLICKER FREE 220-240V 50/60Hz CRI >97 0.00kgs					

L08418 -12



170x85xH88

power	driver	lumen	size(mm)	LEDs	beam angle
12W	300mA	1020lm 4000K	170x85xH88	1	
IP44 DALI FLICKER FREE 220-240V 50/60Hz CRI >97					


Built-in Driver	LED	Accessories				Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 					Matt white Matt black Customized	2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.




INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT

L08419 - 24




power	driver	lumen	size(mm)	LEDs	beam angle
24W	600mA	2040lm 4000K	210x85xH88	2	26°
IP44 DALI 220-240V 50/60Hz CE FLICKER FREE CRI >97					
0.00kgs					

L08420 - 36





power	driver	lumen	size(mm)	LEDs	beam angle
36W	900mA	3060lm 4000K	355x85xH88	3	26°
IP44 DALI 220-240V 50/60Hz CE FLICKER FREE CRI >97					
0.00kgs					

L08421 - 48



power	driver	lumen	size(mm)	LEDs	beam angle
48W	1200mA	4080lm 4000K	220x220xH88	4	26°
IP44 DALI 220-240V 50/60Hz CE FLICKER FREE CRI >97					
0.00kgs					

L07146 - 10



power	driver	lumen	size(mm)	LEDs	beam angle
10W	250mA	850lm 4000K	140*37*H86	5	26°
IP44 DALI 220-240V 50/60Hz CE FLICKER FREE CRI >97					
0.00kgs					



Built-in Driver	LED	Accessories				Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	 					Matt white Matt black Customized	2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.



INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT


L07147 -20



272*37*H86

power	driver	lumen	size(mm)	LEDs	beam angle
20W	500mA	1700lm 4000K	272*37*H86	10	
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					


L07148 -30



405*37*H86

power	driver	lumen	size(mm)	LEDs	beam angle
30W	750mA	2550lm 4000K	405*37*H86	15	
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					


L07150 -9



120xW42xH66

power	driver	lumen	size(mm)	LEDs	beam angle
9W	225mA	765lm 4000K	120xW42xH66	3	
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					

L07151 -15



195xW42xH66

power	driver	lumen	size(mm)	LEDs	beam angle
15W	375mA	1275lm 4000K	195xW42xH66	5	
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					


Built-in Driver	LED	Accessories	Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	OSRAM		Matt white Matt black Customized	2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.



INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT


L07152 - 30



385xW42xH66

power	driver	lumen	size(mm)	LEDs	beam angle
30W	750mA	2550lm 4000K	385xW42xH66	10	26° 45°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					

L07170 - 36



120*120*H90

power	driver	lumen	size(mm)	LEDs	beam angle
36W	900mA	3060lm 4000K	120*120*H90	9	26° 45°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					


L07169 - 16



82*82*H80

power	driver	lumen	size(mm)	LEDs	beam angle
16W	400mA	1360lm 4000K	82*82*H80	4	26° 45°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					

L07167 - 8



51x51x85mm

51x51xH85

power	driver	lumen	size(mm)	LEDs	beam angle
8W	200mA	680lm 4000K	51x51xH85	4	26° 45°
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					


Built-in Driver	LED	Accessories	Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	OSRAM		Matt white Matt black Customized	2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.



INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT

L07168 -14




70x70x85mm

70 x70xH85

power	driver	lumen	size(mm)	LEDs	beam angle
14W	338mA	1148lm 4000K	70 x70xH85	9	
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					


L07142 -18



96*96*H83

power	driver	lumen	size(mm)	LEDs	beam angle
18W	450mA	1530lm 4000K	96*96*H83	9	
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					


L07140 -8



66*66*H83

power	driver	lumen	size(mm)	LEDs	beam angle
8W	200mA	680lm 4000K	66*66*H83	4	
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					
0.00kgs					

L07141 -8



70*H83

power	driver	lumen	size(mm)	LEDs	beam angle
8W	200mA	680lm 4000K	70*H83	4	
IP44 DALI FLICKER FREE					
220-240V 50/60Hz CRI >97					


Built-in Driver	LED	Accessories	Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	OSRAM		Matt white Matt black Customized	2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.





INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT

L07153 - 7





power	driver	lumen	size(mm)	LEDs	beam angle
7W	600mA	595lm 4000K	78xH58	6	
IP44 DALI FLICKER FREE					
CRI >97					

L07154 - 12





power	driver	lumen	size(mm)	LEDs	beam angle
12W	600mA	1020lm 4000K	100xH58	9	
IP44 DALI FLICKER FREE					
CRI >97					

L07155 - 18



power	driver	lumen	size(mm)	LEDs	beam angle
18W	600mA	1530lm 4000K	115xH58	12	
IP44 DALI FLICKER FREE					
CRI >97					

L07156 - 24



power	driver	lumen	size(mm)	LEDs	beam angle
24W	600mA	2040lm 4000K	160xH58	18	
IP44 DALI FLICKER FREE					
CRI >97					


Built-in LED Driver	LED	Accessories	Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	OSRAM		Matt white Matt black Customized	2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.



INTERIOR LED CEILING MOUNTED DOWN SPOTLIGHT


L07159 -18



95xH59

power	driver	lumen	size(mm)	LEDs	beam angle
18W	600mA	1530lm 4000K	95xH59	9	15° 26° 36°
IP44 DALI FLICKER FREE 220-240V 50/60Hz CRI >97					


L07160 -20



112xH60

power	driver	lumen	size(mm)	LEDs	beam angle
20W	600mA	1700lm 4000K	112xH60	12	15° 26° 36°
IP44 DALI FLICKER FREE 220-240V 50/60Hz CRI >97					


L07161 -30



157xH69

power	driver	lumen	size(mm)	LEDs	beam angle
30W	600mA	2550lm 4000K	157xH69	18	15° 26° 36°
IP44 DALI FLICKER FREE 220-240V 50/60Hz CRI >97					

L07162 -40



202xH70

power	driver	lumen	size(mm)	LEDs	beam angle
40W	600mA	3400lm 4000K	202xH70	20	15° 26° 36°
IP44 DALI FLICKER FREE 220-240V 50/60Hz CRI >97					

Built-in LED Driver	LED	Accessories	Finishing	LED color	CRI
Triac dimming 0/1-10V dimming DALI dimming TW dimming	OSRAM		Matt white Matt black Customized	2700K 3000K 4000K 5000K	CRI90+

*It allows you to match the fixture with its surroundings.