


LED GROUND SPOTLIGHT

L00116



- IP67
- Class III
- Surface Mounted
- 300-400mm cable with quick connector.
- Europe Standard CE Certificate. DC12-24V AC12V
- Aluminium materials, powder coated.
- 80° adjustable and 355° rotation
- CRI80 famous branded LED Chips
- Triac I 0/1-10V I DALI dimming
- Remote LED Driver      Flicker Free

VISUAL COMFORT LOW GLARE OPTIC WITH DEEPLY RECESSED LIGHT SOURCE.

Code	System power W	Dimension mm	Cutout mm	Output lm	LEDs pc
L00116 -3	3W	25xH64		195lm 4000K CRI90+	1 PCS


Feature

LED lighting IP67 for outdoor using. Insert into the ground installation. Aluminium materials (#.6063) powder coating - black color finishing as standard. Customized color finishing, power changes are possible depending on the request and the quantity. - Matched main dimming and Dali dimming, Luminaires are available in surface mounted. Lens version, 25 or 60degree output for a better visual comfort. lighting fixture is adjustable and rotatable, suitable for light up anywhere. 35000hours life time.

Remote LED Driver		LED Chips	Accessories	Finishing	LED color	Beam Angle
3W	DC12-24V	OSRAM		Matt black	3000K 4000K 6000K	25° 60°

LED GROUND SPOTLIGHT

L70103



- IP65
- Class III
- Surface Mounted
- 300-400mm cable with quick connector.
- Europe Standard CE Certificate. DC12-24V AC12V
- Aluminium materials, powder coated.
- 80° adjustable and 355° rotation
- CRI80 famous branded LED Chips
- Triac I 0/1-10V I DALI dimming
- Remote LED Driver      Flicker Free

VISUAL COMFORT LOW GLARE OPTIC WITH DEEPLY RECESSED LIGHT SOURCE.

Code	System power W	Dimension mm	Cutout mm	Output lm	LEDs pc
L70103 -5	5W	25xH60		425lm 4000K CRI90+	1 PCS
L70103 -3	3W	25xH60		255lm 4000K CRI90+	1 PCS


Feature

LED lighting IP65 for outdoor using. surface mounted installation. Aluminium materials (#.6063) powder coating - black color finishing as standard Customized color finishing, power changes are possible depending on the request and the quantity. - Matched main dimming and Dali dimming, Luminaires are available in surface mounted. Insert into the ground or recessed can be customized. Lens version, 30degree output for a for better visual comfort. lighting fixture is adjustable and rotatable, suitable for light up anywhere. 35000hours life time.

Remote LED Driver		LED Chips	Accessories	Finishing	LED color	Beam Angle
5W	DC12-24V	OSRAM		Matt black	3000K	30°
3W	DC12-24V				4000K 6000K	

LED GROUND SPOTLIGHT

L70104



- IP67
- Class III
- Surface Mounted
- 300-400mm cable with quick connector.
- Europe Standard CE Certificate. DC12-24V AC12V
- Aluminium materials, powder coated.
- 80° adjustable and 355° rotation
- CRI80 famous branded LED Chips
- Triac I 0/1-10V I DALI dimming
- Remote LED Driver      Flicker Free

VISUAL COMFORT LOW GLARE OPTIC WITH DEEPLY RECESSED LIGHT SOURCE.

Code	System power W	Dimension mm	Cutout mm	Output lm	LEDs pc
L70104 -3	3W	32xH86		195lm 4000K CRI90+	1 PCS

Feature

LED lighting IP67 for outdoor using. Aluminium materials (#.6063) powder coating - black color finishing as standard. Customized color finishing, power changes are possible depending on the request and the quantity. - Matched main dimming and Dali dimming, Luminaires are available in surface mounted. Insert into the ground or recessed can be customized. Lens version, 15, 20, 45, 120degree output for better visual comfort. lighting fixture is adjustable and rotatable, suitable for light up anywhere. 35000hours life time.


Remote LED Driver		LED Chips	Accessories	Finishing	LED color	Beam Angle
3W	DC12-24V	OSRAM		Matt black	3000K 4000K 6000K	15° 20° 45° 120°

LED GROUND SPOTLIGHT

L70105



- IP67
- Class III
- Insert into the ground
- 300-400mm cable with quick connector.
- Europe Standard CE Certificate. DC12-24V AC12V
- Aluminium materials, powder coated.
- 80° adjustable and 355° rotation
- CRI80 famous branded LED Chips
- Triac I 0/1-10V I DALI dimming
- Remote LED Driver      Flicker Free



VISUAL COMFORT LOW GLARE OPTIC WITH DEEPLY RECESSED LIGHT SOURCE.

Code	System power W	Dimension mm	Cutout mm	Output lm	LEDs pc
L70105 -3	3W	32xH86		195lm 4000K CRI90+	1 PCS

Feature

LED lighting IP67 for outdoor using. Aluminium materials (#.6063) powder coating - black color finishing as standard. Customized color finishing, power changes are possible depending on the request and the quantity. - Matched main dimming and Dali dimming, Luminaire is insert into the ground installation, stem length 180mm. Lens version with safety glass, 15, 20, 45, 120degree output for better visual comfort. lighting fixture is adjustable and rotatable, suitable for lighting up anyway where. 35000hours life time.

Remote LED Driver		LED Chips	Accessories	Finishing	LED color	Beam Angle
3W	DC12-24V	OSRAM		Matt black	3000K 4000K 6000K	15° 20° 45° 120°